



BE SURE. BUILD SURE.

Page 1/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 1277 WV - Komponente A**

Article number: 39

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy impregnation

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07 GHS08 GHS09

Signal word

Danger

Hazard-determining components of labelling:

Reaction mass of ethylbenzene and xylene epoxide derivates

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description:

Resin mixture with colouring agents.
Mixture consisting of the following components.

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

(Contd. of page 2)

· Dangerous components:

| | | |
|---|--|--------|
| CAS: 1675-54-3 EINECS: 216-823-5 | epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 | 30-60% |
| EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34 | Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 30-60% |
| CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx | 1-methoxypropan-2-ol Flam. Liq. 3, H226; STOT SE 3, H336 | <10% |

· Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **For safety reasons unsuitable extinguishing agents**

Water with a full water jet.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Open and handle containers with care.
Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.
- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** Keep container tightly closed in a well-ventilated place.

(Contd. on page 5)

GB



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

· Storage class

3

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 107-98-2 1-methoxypropan-2-ol

| | |
|-----|---|
| WEL | Short-term value: 560 mg/m ³ , 150 ppm |
| | Long-term value: 375 mg/m ³ , 100 ppm |
| Sk | |

· DNELs

Reaction mass of ethylbenzene and xylene

| | | |
|------------|------|--|
| Oral | DNEL | 1.6 mg/kg bw/Tag (ArL) mg/kg bw/Tag (Workers) |
| Dermal | DNEL | 180 mg/kg bw/day (ArL) |
| Inhalative | DNEL | 211 mg/m ³ (ArL) |

CAS: 107-98-2 1-methoxypropan-2-ol

| | | |
|------------|------|-----------------------------|
| Oral | DNEL | 3.3 mg/kg bw/Tag (ArL) |
| Dermal | DNEL | 50.6 mg/kg bw/day (ArL) |
| Inhalative | DNEL | 369 mg/m ³ (ArL) |

· CAS No. Designation of material % Type Value Unit

· Additional Occupational Exposure Limit Values for possible hazards during processing:

CAS: 1330-20-7 xylene

| | |
|----------|---|
| WEL | Short-term value: 441 mg/m ³ , 100 ppm |
| | Long-term value: 220 mg/m ³ , 50 ppm |
| Sk; BMGV | |

CAS: 100-41-4 Ethylbenzene

| | |
|-----|---|
| WEL | Short-term value: 552 mg/m ³ , 125 ppm |
| | Long-term value: 441 mg/m ³ , 100 ppm |
| Sk | |

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· Breathing equipment:

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

(Contd. of page 5)

· Hand protection

expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· Material of gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material".

The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

· Eye/face protection

Tight-fitting safety goggles.

Safety goggles.

· Body protection:

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:

Yellow

· Smell:

Characteristic

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

(Contd. of page 6)

| | |
|---|--|
| · Melting point/freezing point: | Not determined |
| · Boiling point or initial boiling point and boiling range | 136 °C (Reaction mass of ethylbenzene and xylene) |
| · Lower and upper explosion limit | |
| · Lower: | 1 Vol % (Reaction mass of ethylbenzene and xylene) |
| · Upper: | 8 Vol % (Reaction mass of ethylbenzene and xylene) |
| · Flash point: | 25 °C |
| · Auto-ignition temperature: | 184 °C |
| · pH | Not determined. |
| · Viscosity: | |
| · Kinematic viscosity at 20 °C | 14 s (DIN 53211/4) |
| · dynamic: | Not determined. |
| · Solubility | |
| · Water: | Not miscible or difficult to mix |
| · Steam pressure at 20 °C: | 8 hPa (Reaction mass of ethylbenzene and xylene) |
| · Vapour pressure at 50 °C: | 45 hPa |
| · Density and/or relative density | |
| · Density at 20 °C | 1.01 g/cm ³ |

· 9.2 Other information

| | |
|--|---|
| · Appearance: | |
| · Form: | Fluid |
| · Important information on protection of health and environment, and on safety. | |
| · Self-inflammability: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/steam mixtures is possible. |

· Information with regard to physical hazard classes

| | |
|--|------------------------------|
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Void |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Flammable liquid and vapour. |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |

(Contd. on page 8)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

(Contd. of page 7)

- | | |
|----------------------------------|------|
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 1675-54-3 epoxide derivates

| | | |
|--------|------|----------------------|
| Dermal | LD50 | 23000 mg/kg (rabbit) |
|--------|------|----------------------|

Reaction mass of ethylbenzene and xylene

| | | |
|------|------|-----------------------|
| Oral | LD50 | 3523-4000 mg/kg (rat) |
|------|------|-----------------------|

| | | |
|--------|------|---------------------|
| Dermal | LD50 | 1100 mg/kg (rabbit) |
|--------|------|---------------------|

| | | |
|------------|----------|---------------|
| Inhalative | LC50/4 h | 11 mg/l (rat) |
|------------|----------|---------------|

CAS: 107-98-2 1-methoxypropan-2-ol

| | | |
|------|------|------------------|
| Oral | LD50 | 4016 mg/kg (rat) |
|------|------|------------------|

| | | |
|--------|------|----------------------|
| Dermal | LD50 | 13000 mg/kg (rabbit) |
|--------|------|----------------------|

| | | |
|------------|----------|-----------------|
| Inhalative | LC50/4 h | 54.6 mg/l (rat) |
|------------|----------|-----------------|

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

(Contd. of page 8)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 1675-54-3 epoxide derivates

| | |
|-----------|-------------------------------------|
| IC50 | >42.6 mg/l (Bak) |
| LC50/96h | 2 mg/l (Oncorhynchus mykiss) |
| EC50/48h | 1.8 mg/l (Daphnia magna) |
| ErC50/72h | 11 mg/l (Selenastrum capricornutum) |

Reaction mass of ethylbenzene and xylene

| | |
|----------|--------------------------------------|
| EC50/72h | 2.2 mg/l (Selenastrum capricornutum) |
| LC50/96h | 2.6 mg/l (Oncorhynchus mykiss) |
| NOEC | 16 mg/l (BEL) |

CAS: 107-98-2 1-methoxypropan-2-ol

| | |
|----------|----------------------------|
| IC50 | 1000 mg/l (BEL) |
| LC50/96h | 6812 mg/l (Leucidus idus) |
| LC50/48h | 23300 mg/l (Daphnia magna) |
| EC50/48h | 23300 mg/l (Daphnia magna) |

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

(Contd. of page 9)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1139

14.2 UN proper shipping name

ADR COATING SOLUTION, ENVIRONMENTALLY HAZARDOUS
IMDG COATING SOLUTION, MARINE POLLUTANT
IATA COATING SOLUTION

14.3 Transport hazard class(es)

ADR
Class 3 (F1) Flammable liquids.
Label 3

IMDG, IATA

Class 3 Flammable liquids.
Label 3

14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards:

Product contains environmentally hazardous substances: epoxide derivates

Marine pollutant:

Yes
Symbol (fish and tree)

Special marking (ADR):

Symbol (fish and tree)

14.6 Special precautions for user

Warning: Flammable liquids.

Kemler Number:

30

EMS Number:

F-E, S-E

Stowage Category

A

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

(Contd. of page 10)

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

· Transport category

3

· Tunnel restriction code

D/E

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

· UN "Model Regulation":

UN 1139 COATING SOLUTION, 3, III,
ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Qualifying quantity (tonnes)
for the application of lower-
tier requirements

200 t

· Qualifying quantity (tonnes)
for the application of upper-
tier requirements

500 t

· 15.2 Chemical safety
assessment:

A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1277 WV - Komponente A

(Contd. of page 11)

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H226 Flammable liquid and vapour.
 - H304 May be fatal if swallowed and enters airways.
 - H312 Harmful in contact with skin.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H373 May cause damage to organs through prolonged or repeated exposure.
 - H411 Toxic to aquatic life with long lasting effects.
 - EUH205 Contains epoxy constituents. May produce an allergic reaction.

- **Department issuing data specification sheet:**

Environment protection department.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

- * Data compared to the previous version altered.

GB